

# ALKLEN

## Description:

**ALKLEN** is a white, free-flowing granular material. It is designed for intermediate alkaline, soak, or circulation cleaning in bakeries, dairies, and other food processing facilities where aluminum and other soft metals contraindicate the use of many cleaners.

## Typical properties:

- pH of a 1% solution—about 11.0-11.5
- Color—A white granular material
- Odor—None
- Contains powerful water softeners
- Prevents stone and scale build-up
- Excellent wetting and rinsing properties
- SAFE for use on aluminum, tin, and painted surfaces.
- Superior penetrating and soil suspension properties.
- Low foaming, non fuming, no boil-back.

## Uses:

**ALKLEN** is to be used to CIP tanks and lines; COP cleaning of parts and other miscellaneous equipment; various high-pressure cleaning needs; and mechanical or circulation cleaning of bake pans, cans, cases, meat racks, and aluminum cookware and utensils.

## How to use:

CIP and HIGH PRESSURE: Use 1/3 ounce per gallon of water at 130-140°F/55-60°C  
COP, MECHANICAL, CIRCULATION, and CAN WASHING: Use 1/3 ounce per gallon of water at 130-160°F/55-71°C.  
GENERAL PURPOSE: Use 1/3-3/4 ounce per gallon of water at 120-130°F/49-55°C.  
NOTE: Rinse well after use with warm water and sanitize as needed. MORE or LESS **ALKLEN** may be needed depending on soil load and wash conditions.

## Containers:

**ALKLEN** is available in 400# drums. PLEASE thoroughly read MSDS prior to use, and use all appropriate safety/PPE gear.

## DISTRIBUTED BY:

For pricing and availability in your area, please contact:



*Chemical and Supply Company*

Phone (847)-912-8384  
Fax: (847)-947-2574

Or email at  
Steve@mistchem.com  
or visit www.mistchem.com

## MANUFACTURED BY:



Greendale, WI 53129  
(414)-325-8100  
bmoffatt@camcochemical.com

